

## Glazing of partition panels

# DOUBLE-SIDED ADDITIONAL GLAZING OF METAL PARTITION







It is inserted into the existing partition panels, thickness 60, 80, 100 and 120 mm.

The window consists of a reinforcing profile, covering frames and sheet glass, thickness 4 or 6 mm.

## **TECHNICAL DATA**

Туре	
additional double-sided Pharma glazing	

Panel thickness	
value	surface density
100 mm	37 kg/m2
120 mm	38 kg/m2
60 mm	39 kg/m2
80 mm	40 kg/m2
atypical	kg/m2
For partitions with a thickness of more than 20	mm, consultation with production is required.

height 1200 mm
1200 mm
1500 mm
1200 mm
1500 mm
1200 mm
1500 mm

Maximum structural opening dimensions 1500x1800 mm! – Glazing must be fitted across the two panels. This is an atypical design, it is recommended to always consult the production department. Min. height 800 mm, max. dimension 1500 mm.

### Glazing

laminated safety glass, thickness 6 mm

atypical

#### float glass, thickness 4 mm

Note: As standard the glazing is of clear glass, but it is possible to order an atypical version with milk glass. Float glass design only for glazing with sill 1100mm and above.

#### Version

with inner frame

atypical

#### Frame hue and material

metal sheet, hue RAL 9002

#### metal sheet, hue RAL 9016

Stainless steel AISI 304

Komaxit, hue RAL

### **Atypical design**

#### Type design

Atypical design

Type design

0 - Unique specification out of offered versions

Atypical design

Q - atypical design that cannot be uniquely specified by a code

## MORE INFORMATION, PHOTOS

