

Glazing of partition panels

SINGLE-SIDED ADDITIONAL GLAZING OF METAL PARTITION



It is inserted into the existing partition panels, thickness 60, 80, 100 and 120 mm.

The window consists of a reinforcing profile, covering frames and sheet glass, thickness 4 or 6 mm.

TECHNICAL DATA

Type

additional single-sided Pharma glazing

Panel thickness

thickness	surface density
100 mm	23 kg/m ²
120 mm	24 kg/m ²
60 mm	21 kg/m ²
80 mm	22 kg/m ²

Structural opening dimensions

1200 mm
1500 mm
1200 mm
1500 mm
1200 mm
1500 mm
Min. height 800 mm, max. dimension 1500 mm.

Glazing

laminated safety glass, thickness 6 mm

atypical design

float glass, thickness 4 mm

Note: As standard the glazing is of clear glass, but it is possible to order an atypical version with milk glass.
Float glass design only for glazing with sill 1100mm and above.

Frame hue and material

metal sheet, hue RAL 9002

metal sheet, hue RAL 9016

Stainless steel AISI 304

Komaxit, hue RAL

Atypical design

Type design

Atypical design

Type design

0 - Unique specification out of offered versions

Atypical design

Q - atypical design that cannot be uniquely specified by a code

MORE INFORMATION, PHOTOS

