


cat. no. 103.09

Systems for transfer

## THE SLIDING WINDOW



The sliding window is one of the basic components for building clean areas and workplaces with maximum safety, sterility, hygiene, easy maintenance and sanitation.

Its design is mainly suitable for areas in the pharmaceutical industry and in healthcare facilities.

### TECHNICAL DATA

#### Type of product

The sliding window

#### Assembly thickness

60 mm

The thickness of the sliding window assembly is not adjusted to the wall into which it is installed. The window thickness is always 60 mm.

#### Pass - through opening dimensions

width	height
700 mm	750 mm
940 mm	750 mm

The standard window dimensions are 940 x 750 mm. An agreement can be made on the manufacture of a window of atypical dimensions and design.

## Glazing

### Safety glass 6mm thick

Without glazing (solid tile)

Atypical

## Cover shade and material

### Metal sheet, hue RAL 9016

Stainless steel AISI304

Komaxit, hue RAL

## Window sill

double-sided

### single-sided

without a sill

atypical

The sill desk for the sliding window consists of 2 pieces of the facing in stainless design with a laminated board filler 21 mm thick

## Atypical design

Type design

Atypical design

Type design

0 - Unique specification out of offered versions

Atypical design

Q - atypical design that cannot be uniquely specified by a code

## MORE INFORMATION, PHOTOS

