

Partition panels and their accessories

BASIC PARTITION PANELS







Basic partition panels represent one of the basic elements to construct clean workplaces and areas with maximum safety, sterility, hygiene, easy maintenance and sanitation.

Their design is suitable especially for hospital environments, areas in pharmaceutical industry, electrotechnical industry, mechanical engineering industry, food industry, and chemical industry.

Due to the tight connection between the partition panels, spaces created between the panels, the floor and the ceiling are guaranteed to contain overpressure or underpressure in the room, which means that they meet the basic criteria for clean areas, for which these panels were specifically designed and proven.

TECHNICAL DATA

Panel thickness
100 mm
120 mm
32 mm
52 mm
60 mm
80 mm

Panel width W

1190 mm

560 mm

The project allows the use of atypical panels with the dimension of min. 300 mm and max. 1190 mm.

Panel height H

2550 mm

2750 mm

3050 mm

Height according to standard dimensional range 2550, 2750, 3050 mm. Preferred dimensions 2550, 2750, 3050 mm. Min. dimension 300 mm, max. dimension 4000 mm.

Number of cable glands

no cable gland

2 pcs (1 pc 85 mm from the left- 1 pc 85 mm from the right)

cable glands from the left, cable glands from the right

Filler

Mineral wool

PSE - foam polystyrene

Atypical

Facing hue and material - standard on the visible side

Galvanized metal sheet, hue RAL 1015

Galvanized metal sheet, hue RAL 6027

Galvanized metal sheet, hue RAL 9002

Galvanized metal sheet, hue RAL 9016

Stainless steel AISI 304

Aluminum sheet, hue RAL

Powder coating (Komaxit), hue RAL

Facing hue and material - standard on the rear side

Galvanized metal sheet, hue RAL 1015

Galvanized metal sheet, hue RAL 6027

Galvanized metal sheet, hue RAL 9002

Galvanized metal sheet, hue RAL 9016

Stainless steel AISI 304

Aluminum sheet, hue RAL

Powder coating (Komaxit), hue RAL

MORE INFORMATION, PHOTOS

