

Ceiling

WALKABLE TILE SUSPENDED CEILING



This walkable tile suspended ceiling is designed for the construction of suspended ceilings where limited movement of persons on the top side of the suspended ceiling is expected during installation and service work.

The walkable tile suspended ceiling consists of sheet metal tiles and suspension brackets. The tiles are mounted individually by means of threaded bars and do not require any auxiliary suspension grid. The structure of the suspended ceiling allows for direct mounting of light fixtures, HVAC adapters, PUROFIL filtration adapters.

TECHNICAL DATA

Suspended ceiling type

Walkable tile suspended ceiling

Dimension

Standard dimensions

Standard dimensions

Atypical dimensions WxH

Values in mm for the sides of the tile (W x D).

Tile type
Tile with a hole for a light fixture 625x625
Tile with a hole for a light fixture 312x625
Tile with atypical dimensions
Solid tile
Atypical
Tile with a hole

Tile hole dimensions
Tile hole dimensions
Hole diameter
Without a hole
Atypical - multiple holes in a tile (see the drawing in the specifications)

Distance of the hole centre from the tile edge
Without hole
Distance of the hole centre from the tile edge
X x Y - Length values in X (horizontal) and Y (vertical) axis determine the centre of the tile hole from the tile edge (ALWAYS THE BOTTOM LEFT CORNER OF THE TILE!!)

Threaded bar length
Long threaded bars with the length of 2000mm
Standard threaded bars with the length of 1000mm

Hue of standard tiles
Galvanized steel sheet, hue RAL 9002
Galvanized steel sheet, hue RAL 9015
Powder coating (Komaxit), hue RAL

Atypical design
Type design
Atypical design
Type design 0 - Unique specification out of offered versions Atypical design Q - atypical design that cannot be uniquely specified by a code

MORE INFORMATION, PHOTOS

